

“SMART” LED ROUND GARAGE

Integrated Controls Solution

MHTL-RGL SMART SERIES

Project _____

Part No. _____

Quantity _____

- Maximize efficiency, save on-site labor costs and controls coordination headaches. MHT’s fully integrated photocontrol, occupancy sensor and dimming ability can save up to 90% in energy costs! Making it the “Smart” Solution.

- Our proven “Smart” LED solutions offer incredible value, proven reliability and are backed by our 10-year warranty.



APPLICATIONS

- Canopy
- Parking Garage
- Manufacturing
- Warehouse
- Walkway



FEATURES

- Integrated Photocontrol that Turns OFF Lighting When Sufficient Daylight is Available
- Integrated Motion Sensor that Reduces Light Output When An Area is Unoccupied
- Dimming Range Between 10% and 50% When Motion is Not Detected
- Different Lens Options for up to 20ft Mounting Height and 40ft Diameter Coverage
- Optional Remote Control for On-Site Motion Sensor Adjustment
- L90 > 180,000 Hours (38W & 48W); L90 > 75,000 Hours (72W)
- Die Cast Aluminum Housing (Matte White)
- High Performance Acrylic Optical Lens
- Surface Mount Bracket - Easy Installation & Maintenance
- Fixture Protection Class IP65

LED/DRIVER

- Standard Input Voltage 120/277V
- Power Factor > 0.93 @277V
- THD < 12% @277V
- Color Temperature 4000K/5000K
- 6kV Surge Protection
- CRI > 75

Model	Input Power	Module	Lm/W	Lumen	Dimensions
MHTL-RGL-38E-4K-U	38W	1	>113	>3,900	Ø15” x 5.4”
MHTL-RGL-48E-4K-U	48W	2	>120	>5,500	Ø15” x 5.4”
MHTL-RGL-50E-4K-U	50W	1	>102	>4,900	Ø15” x 5.4”
MHTL-RGL-72E-4K-U	72W	2	>126	>9,000	Ø15” x 5.4”



Manufactured in the USA

Toll Free **888-511-7780** • www.mhtlighting.com



